

NEW GENERATION

YellowScan Surveyor Ultra.

The new and improved second generation of Surveyor Ultra integrating Hesai's XT32M2X scanner

Expect better accuracy, precision, intensity, and lighter weight than its predecessor.

With the combination of a proven inertial and navigation system and a multi-channel 360° laser scanner, this new version is ready to show it all.



Technologies inside





Key differentiators

- High point density
- Outstanding scanner range
- Fly&Drive ready



Integrations

- Multirotor drones
- Helicopter drones
- Fixed-wings
- Land vehicles

PRELIMINARY DATASHEET

Technical specifications.

| Scanner | Hesai XT32M2X |
|--------------------------------------|---------------|
| Laser range @10% target reflectivity | 140 m |
| Precision ^{(1) (3)} | 3 cm |
| Accuracy ^{(2) (3)} | 3 cm |
| Scanner field of view | 360° |
| Shots per second | 640k |
| Echoes per shot | Up to 3 |
| GNSS-Inertial | Applanix |
| solution | APX-15 UAV |

General characteristics

| Weight | 1.32 kg (2.92 lbs) battery included |
|-----------------------|-------------------------------------|
| Autonomy | 1:20 hour typ. |
| Power consumption | 22 W |
| Operating temperature | -10 to +40 °C |
| Size | L 16 x W 10.3 x H 13.8 cm |

⁽¹⁾ Precision, also called reproducibility or repeatability, accounts for the variation $% \left(1\right) =\left(1\right) \left(1\right)$ in successive measurements taken on the same target.

Package includes.

Hardware:

- YellowScan Surveyor Ultra
- Charger and 2 batteries
- GNSS antenna and cable
- 2 USB flash drives
- Documentation

Services:

- Boresight calibration certificate
- 1-year warranty
- In-person training
- Worldwide technical and operational support


Software:

- Applanix POSPac UAV, to post-process GNSS and inertial data for highest accuracy
- YellowScan CloudStation, to generate and visualize your georeferenced point cloud

+ Optional:

- Mounting bracket with single or dual Sony α6000 camera for DJI M600
- DJI skyport or Gremsy quick release adapters
- YellowScan LiveStation, the real-time in-flight LiDAR monitoring kit (software + 2 radio-modems)
- Warranty and technical support extensions
- YellowScan Fly & Drive

Typical mission parameters.






FLIGHT SPEED 5-30 m/s



ALTITUDE 90 m



SWATH 312 m



⁽²⁾ Accuracy is the degree of conformity of a measured position to its actual (true) value. (3) One σ @ 50 m, nadir.